

ESD masking tape antistatic, unprinted, 24 mm x 55 m

Item no. EP0603036

Manufacturer A1-ESD

Antistatic, waterproof crepe masking tape with no print and a surface resistance of 10^{11} ohm. 24 mm wide, ideal for masking and taping in the ESD work area.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Certification	IEC 61340-5-1
ESD equipment	ESD Kreppband
Sales unit	Rolle 55 m
Weight	0.1 kg
Width	24



STANDARDS & COMPLIANCE

ESD safe IEC 61340-5-1

DESCRIPTION

The antistatic crepe tape is used for masking, taping and bundling in the EPA without disturbing the protection of the workstation. The waterproof crepe surface tears cleanly by hand.

YOUR BENEFITS

- Antistatic with a surface resistance of 10^{11} ohm
- Waterproof crepe surface, tearable by hand
- Unprinted, can be written on

TECHNICAL DATA

- Material: crepe paper, antistatic
- Surface resistance: 10^{11} ohm
- Width: 24 mm
- Length: 55 m
- Paper core diameter: 76 mm

APPLICATION

Masking, taping and labelling in EPA areas of electronics manufacturing.

STANDARDS AND COMPLIANCE

Suitable for use in an EPA in accordance with IEC 61340-5-1.