

Curve KE 2/180 LS for Transfer System TS 2plus, ESD-Compatible - Bosch Rexroth 3842999037

Item no. BRR-3842999037

Manufacturer Bosch Rexroth

The Curve KE 2/180 LS redirects workpiece pallets through 180 degrees within the Bosch Rexroth TS 2plus transfer system. Supplied partially assembled with inner guide and drive motor included, it supports workpiece pallet total weights up to 20 kg and accommodates transport lengths from 160 to 400 mm. ESD-compatible design makes it suitable for electrostatically sensitive assembly environments.

TECHNICAL DATA

Country of Manufacture **Germany**

HS-Code **84283300**

Weight **0.1 kg**



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Curve KE 2/180 LS is a 180-degree diverting unit for the Bosch Rexroth TS 2plus transfer system. Designed for ESD-sensitive production and assembly environments, it handles workpiece pallets with a total weight of up to 20 kg. The unit ships partially assembled with the inner guide and drive motor already included, reducing on-site installation effort.

- 180-degree curve for the TS 2plus transfer system
- ESD-compatible for electrostatically sensitive assembly lines
- Supports workpiece pallet total weights up to 20 kg
- Length in direction of transport (IT): 160, 240, 320 or 400 mm
- Compatible with all b x IT combination options
- Partially assembled - inner guide and motor included in delivery

TECHNICAL DATA

Specification	Value
Type	KE 2/180 LS
System	Transfer System TS 2plus

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Specification	Value
Deflection angle	180 degrees
ESD-compatible	Yes
Max. workpiece pallet total weight [mG]	20 kg
Length in direction of transport [IT]	160 / 240 / 320 / 400 mm
Preferred values	160 / 240 / 320 / 400 mm
Scope of delivery	Curve complete with drive motor, inner guide included
Delivery condition	Partially assembled
Recommended accessories	Connection Kits, Section supports SZ 2/...