

ErsaDUR Soldering Tip, Hollow 2.3 mm, i-Tool MK2 & Trace - Ersa 0142WDLF23

Item no. ER-0142WDLF23

Manufacturer Ersa

EAN 4003008149142

ErsaDUR long-life soldering tip, series 142, hollow form 2.3 mm, with bayonet mount for i-Tool MK2 and i-Tool Trace. Tool-free Tip'n'Turn tip change, suitable for leaded and lead-free soldering.

TECHNICAL DATA

Country of Manufacture **Germany**

Weight **0.1 kg**


DESCRIPTION

ErsaDUR soldering tip, hollow form 2.3 mm, with bayonet mount (Tip'n'Turn) for the i-Tool MK2 generation.

Suitable for the following soldering irons:

- i-Tool pico MK2, nano MK2, i-Tool MK2, TRACE
- 0105CDJ soldering iron MK2, 150 W
- 0140CDJ soldering iron Trace, 150 W
- 0125CDK soldering iron MK2, 80 W
- 0135CDK soldering iron MK2, 80 W

The patented ErsaDUR coating is designed for demanding industrial applications in continuous use and is suitable for both leaded and lead-free soldering. Thanks to the Tip'n'Turn concept, tool-free tip changes are done in record time - by hand or with the 0A58 holding stand; no additional tip fastening is required.

Tip and heating element are changed separately, so the high-quality heating element is retained - making the system both ecologically and economically sustainable. The printed barcode simplifies integrating the tip into the soldering programs of the i-CON TRACE Cockpit.

Note: not compatible without an iron replacement with the 0100CDJ i-Tool 150 W, 0130CDK i-Tool PICO 80 W and 0120CDK i-Tool Nano 80 W (stations with a light/silver front panel).

TECHNICAL DATA

Tip form	Hollow
Tip diameter/width	2.30 mm
Tip version	straight
Shaft outer diameter	7.70 mm
Shaft inner diameter	5.30 mm
Overall length	46 mm
Coating	ErsaDUR long-life tip
Tip series	142
RoHS compliant	Yes