

ESD cartridge soldering tip bevel 45° 3 mm for TS1200 - Quick TSS02-3C

Item no. QCK-TSS02-3C

Manufacturer Quick

EAN 4250078320883

Cartridge soldering tip for the Quick TS1200, bevelled tip 45°, tip width 3 mm. The integrated sensor and directly bonded heater give fast, stable temperature control and long service life. Lead-free capable, RoHS compliant.

TECHNICAL DATA

Ausführungsklasse	ESD (antistatic)
Country of Manufacture	China
HS-Code	85159080900
Weight	0.1 kg



STANDARDS & COMPLIANCE

ESD safe

DESCRIPTION

The Quick TSS02-3C is a Rapid cartridge soldering tip for the Quick TS1200 soldering station, straight, bevelled tip 45° with 3 mm tip width. The integrated temperature sensor and directly bonded heater deliver high efficiency and temperature stability, protecting the tip.

KEY BENEFITS

- Temperature sensor integrated right in the tip for fast energy sensing
- Tip and heater directly bonded for high temperature stability
- Automatic per-cartridge temperature matching with the Quick TS1200
- Gentle operation for longer service life

TECHNICAL DATA

Version	straight
Tip shape	bevel 45°
Tip width	3 mm
Tip series	TSS02
Weight	approx. 0.1 kg

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

APPLICATIONS

For soldering work on the ESD-capable Quick TS1200 station in electronics manufacturing, repair and prototyping.

COMPATIBILITY AND SCOPE OF DELIVERY

- Fits the Quick TS1200 soldering station
- Soldering tip series TSS02
- Geometry: bevel 45°, 3 mm
- Scope of delivery: 1 cartridge soldering tip

Conformity: RoHS, lead-free capable, ESD-safe. Origin: China.