

ACE MC 4550 EUM2-HT. shock absorber, M 45x1,5, stroke 50 mm, High temperature, self-adjusting

Item no. FL-MC-4550-EUM2-HT

Manufacturer ACE

EAN 4050571481698

ACE shock absorber, M 45x1,5, stroke 50 mm, High temperature, self-adjusting

TECHNICAL DATA

HS-Code 84879059

Weight 1.4 kg



DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hard chromium-plated steel, head: hardened and bronzed steel, compression spring: zinc plating or KU-coated

Temperature range:

-12°C to max. +66°C

Stroke speed:

0,15 to 5 m/s (upon request, up to 20 m/s)

Fixed limit stop:

integrated

Optional:

High temperature version (0°C up to max. +150°C) **-HT**, low temperature version (-50°C up to max. +66°C) **-LT**

Version	High temperature, self-adjusting
Thread B	M 45x1,5
Stroke [mm]	50
max. Energy consumption per stroke (W3) [Nm]	740

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

max. Energy consumption per hour (W4) [Nm]	112000
effective mass (me) [KGM]	150 - 620
Spring force [N]	70 - 145
A [mm]	146,5
C [mm]	48,5
D [mm]	35
Max. axial deviation* [°]	3
Impact head	PP 45
clamping flange	QF 45
Side load adapter**	BV 4550
Locking nut	NM 45
Temperature range [°C]	0 to +150