

## ACE MC 4575 EUM0. shock absorber, M 45x1,5, stroke 75 mm, Standard, self-adjusting

Item no. FL-MC-4575-EUM0

Manufacturer ACE

EAN 4050571481728

ACE shock absorber, M 45x1,5, stroke 75 mm, Standard, self-adjusting

### TECHNICAL DATA

HS-Code 84879059

Weight 1.5 kg



### DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hard chromium-plated steel, head: hardened and bronzed steel, compression spring: zinc plating or KU-coated

Temperature range:

-12°C to max. +66°C

Stroke speed:

0,15 to 5 m/s (upon request, up to 20 m/s)

Fixed limit stop:

integrated

Optional:

High temperature version (0°C up to max. +150°C) **-HT**, low temperature version (-50°C up to max. +66°C) **-LT**

|                                              |                          |
|----------------------------------------------|--------------------------|
| Version                                      | Standard, self-adjusting |
| Thread B                                     | M 45x1,5                 |
| Stroke [mm]                                  | 75                       |
| max. Energy consumption per stroke (W3) [Nm] | 1130                     |

**esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                                            |                       |
|--------------------------------------------|-----------------------|
| max. Energy consumption per hour (W4) [Nm] | 146000                |
| effective mass (me) [KGM]                  | 20 - 80               |
| Spring force [N]                           | 50 - 180              |
| A [mm]                                     | 172,1                 |
| C [mm]                                     | 73,9                  |
| D [mm]                                     | 35                    |
| Max. axial deviation* [°]                  | 2                     |
| Impact head                                | <a href="#">PP 45</a> |
| clamping flange                            | <a href="#">QF 45</a> |
| Locking nut                                | <a href="#">NM 45</a> |
| Temperature range [°C]                     | -12 to +66            |