

ACE MC 600 EUMH2. shock absorber, M 25x1,5, self-adjusting, stroke 25,4 mm

Item no. FL-MC-600-EUMH2

Manufacturer ACE

EAN 4050571481865

ACE shock absorber, M 25x1,5, self-adjusting, stroke 25,4 mm

TECHNICAL DATA

HS-Code 84879059

Weight 0.27 kg



DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hardened, stainless steel, roller type diaphragm: ethylene-propylene

Temperature range:

0 to +66 °C

Stroke speed:

0,06 to 6 m/s

Fixed limit stop:

integrated

Information:

Exceeding W4: (max. energy absorbed per hour expressed in Nm/h) is possible when switched off temporarily or the shock absorber is cooled with the cylinder exhaust air (take note of the approved heating)

Thread B	M 25x1,5
Stroke [mm]	25,4
max. Energy consumption per stroke (W3) [Nm]	136

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

max. Energy consumption per hour (W4) [Nm]	68000
effective mass (me) [KGM]	400 - 2300
Spring force [N]	5 - 10
A [mm]	7,3
C [mm]	110,3
E [mm]	10
G [mm]	8,0
I [mm]	30,5
SW1 [mm]	10
SW2 [mm]	30
Max. axial deviation* [°]	2
Impact head	PP 600
clamping flange	MB 25
Stop sleeve	AH 25
Side load adapter**	BV 25
Locking nut	KM 25