

ACE MC 6450 EUM3-HT. shock absorber, M 64x2, stroke 50 mm, High temperature, self-adjusting

Item no. FL-MC-6450-EUM3-HT

Manufacturer ACE

EAN 4050571482053

ACE shock absorber, M 64x2, stroke 50 mm, High temperature, self-adjusting

TECHNICAL DATA

HS-Code	84879059
Weight	3.2 kg



DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hard chromium-plated steel, head: hardened and bronzed steel, compression spring: zinc plating or KU-coated

Temperature range:
-12°C to max. +66°C

Stroke speed:
0,15 to 5 m/s (upon request, up to 20 m/s)

Fixed limit stop:
integrated

Optional:
High temperature version (0°C up to max. +150°C) **-HT**, low temperature version (-50°C up to max. +66°C) **-LT**

Version	High temperature, self-adjusting
Thread B	M 64x2
Stroke [mm]	50
max. Energy consumption per stroke (W3) [Nm]	1870

max. Energy consumption per hour (W4) [Nm]	146000
effective mass (me) [KGM]	1600 - 6300
Spring force [N]	90 - 155
A [mm]	176,4
C [mm]	48,6
D [mm]	48
Max. axial deviation* [°]	4
Impact head	PP 64
clamping flange	QF 64
Side load adapter**	BV 6450
Locking nut	NM 64
Temperature range [°C]	0 to +150