

ACE MC 75 EUM4. shock absorber, M 12x1, self-adjusting, stroke 10 mm

Item no. FL-MC-75-EUM4

Manufacturer ACE

ACE shock absorber, M 12x1, self-adjusting, stroke 10 mm

TECHNICAL DATA

HS-Code 84879059

Weight 0.035 kg



DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hardened, rust-free steel

Temperature range:

-10 to +66 °C

Stroke speed:

0,15 to 4 m/s

Fixed limit stop:

integrated

Information:

Exceeding W4 (max. energy consumed per hour expressed in Nm/h) is possible in the case of temporary switch-off, or when the shock absorber is cooled with the cylinder exhaust air (take note of the approved heating).

Thread B M 12x1

Stroke [mm] 10

max. Energy consumption per stroke (W3) [Nm]	9
max. Energy consumption per hour (W4) [Nm]	28200
effective mass (me) [KGM]	25 - 72
Spring force [N]	4 - 9
A [mm]	5,0
E [mm]	52,0
F [mm]	5,0
G [mm]	3,2
I [mm]	18,0
J [mm]	3
K [mm]	7,6
SW2 [mm]	14
Max. axial deviation* [°]	2
clamping flange	MB 12
Stop sleeve	AH 12
Side load adapter**	BV 12
Locking nut	KM 12