

ACE MC 9 EUM1B. shock absorber, M 6x0,5, self-adjusting, stroke 5 mm

Item no. FL-MC-9-EUM1B

Manufacturer ACE

EAN 4050571482107

ACE shock absorber, M 6x0,5, self-adjusting, stroke 5 mm

TECHNICAL DATA

HS-Code 84879059

Weight 0.0036 kg



DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hardened, rust-free steel

Temperature range:

-10 to +66 °C

Stroke speed:

0,15 to 4 m/s

Fixed limit stop:

integrated

Information:

Exceeding W4 (max. energy consumed per hour expressed in Nm/h) is possible in the case of temporary switch-off, or when the shock absorber is cooled with the cylinder exhaust air (take note of the approved heating).

Thread B	M 6x0,5
Stroke [mm]	5
max. Energy consumption per stroke (W3) [Nm]	1

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

max. Energy consumption per hour (W4) [Nm]	2000
effective mass (me) [KGM]	0,6 - 3,2
Spring force [N]	2 - 4
A [mm]	2,5
E [mm]	26,0
F [mm]	2,5
G [mm]	2,0
I [mm]	10,0
J [mm]	2
K [mm]	4,8
SW2 [mm]	8
Max. axial deviation* [°]	2
clamping flange	MB 6 SC2
Stop sleeve	AH 6
Locking nut	KM 6