

ACE SC 4550 EUM6. shock absorber, M 45x1,5, self-adjusting, stroke 50 mm

Item no. FL-SC-4550-EUM6

Manufacturer ACE

EAN 4050571611613

ACE shock absorber, M 45x1,5, self-adjusting, stroke 50 mm

TECHNICAL DATA

HS-Code 40094100

Weight 1.9 kg



DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hardened, rust-free steel (type SC 45...: steel hard chrome plated)

Temperature range:

0°C to max. +66°C (SC 45...: -12°C to max. +66°C)

Stroke speed:

0,15 up to 3,7 m/s (Type SC²: 0,1 up to 5,7 m/s, Type SC 45...: 0,02 up to 0,46 m/s)

Fixed limit stop:

integrated

Information:

Exceeding W4: (max. energy absorbed per hour expressed in Nm/h) is possible when switched off temporarily or the shock absorber is cooled with the cylinder exhaust air (take note of the approved heating)

Thread B	M 45x1,5
Stroke [mm]	50
max. Energy consumption per stroke (W3) [Nm]	680

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

max. Energy consumption per hour (W4) [Nm]	112000
effective mass (me) [KGM]	11800 - 27000
Spring force [N]	47 - 242
D [mm]	216,5
E [mm]	9,5
G [mm]	12,6
I [mm]	48,5
K [mm]	35
Max. axial deviation* [°]	3
Temperature range [°C]	-12 to +66