

ACE SC 650 EUM3. shock absorber, M 25x1,5, self-adjusting, stroke 25 mm

Item no. FL-SC-650-EUM3

Manufacturer ACE

EAN 4050571611668

ACE shock absorber, M 25x1,5, self-adjusting, stroke 25 mm

TECHNICAL DATA

HS-Code 84879059

Weight 0.33 kg



DESCRIPTION

Materials:

shock absorber body and accessory: Steel bronzing, piston rod: hardened, rust-free steel (type SC 45...: steel hard chrome plated)

Temperature range:

0°C to max. +66°C (SC 45...: -12°C to max. +66°C)

Stroke speed:

0,15 up to 3,7 m/s (Type SC²: 0,1 up to 5,7 m/s, Type SC 45...: 0,02 up to 0,46 m/s)

Fixed limit stop:

integrated

Information:

Exceeding W4: (max. energy absorbed per hour expressed in Nm/h) is possible when switched off temporarily or the shock absorber is cooled with the cylinder exhaust air (take note of the approved heating)

Thread B	M 25x1,5
Stroke [mm]	25
max. Energy consumption per stroke (W3) [Nm]	73

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

max. Energy consumption per hour (W4) [Nm]	68000
effective mass (me) [KGM]	68 - 408
Spring force [N]	11 - 32
A [mm]	7,0
D [mm]	106,4
E [mm]	10,0
G [mm]	6,3
I [mm]	36,3
J [mm]	4,6
K [mm]	23
SW1 [mm]	23
SW2 [mm]	30
Max. axial deviation* [°]	5
Clamping flange****	MB 25
Stop sleeve	AH 25
Side load adapter***	BV 25 SC
Locking nut	KM 25
Temperature range [°C]	0 to +66