

# Airtec DSWPVM 32/320. Round cylinder, piston 32 mm, stroke 320 mm

Item no. FL-DSWPVM-32/320

Manufacturer Airtec

EAN 4050571276126

Round cylinder, piston 32 mm, stroke 320 mm

## TECHNICAL DATA

HS-Code 84123100

Weight 0.95 kg



## DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: hard chromium plated steel, seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

|                       |                                 |
|-----------------------|---------------------------------|
| Piston diameter [mm]  | 32                              |
| Stroke [mm]           | 320                             |
| Version               | adjustable end position damping |
| A (piston rod thread) | M 10                            |
| B (fastening thread)  | M 30x1,5                        |

**esd.equipment**

Keldersstr. 15  
42697 Solingen, Deutschland  
VAT ID: DE269659389

Phone: +49 212 38340680  
shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                         |        |
|-------------------------|--------|
| G (compressed air port) | G 1/8" |
| B1 [mm]                 | 7      |
| B2 [mm]                 | 35     |
| D1 [mm]                 | 45     |
| D2 [mm]                 | 12     |
| D4 [mm]                 | 38     |
| D5 [mm]                 | 30     |
| D6 [mm]                 | 33,6   |
| D7                      | M 8x1  |
| F [mm]                  | 20     |
| K [mm]                  | 38     |
| L1 [mm]                 | 148    |
| L2 [mm]                 | 47     |
| L3 [mm]                 | 78     |
| L4 [mm]                 | 30     |
| L5 [mm]                 | 14     |
| CH [mm]                 | 10     |