

Airtec DSWPVM 40/25. Round cylinder, piston 40 mm, stroke 25 mm

Item no. FL-DSWPVM-40/25

Manufacturer Airtec

EAN 4050571276232

Round cylinder, piston 40 mm, stroke 25 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.9 kg



DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: hard chromium plated steel, seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm]	40
Stroke [mm]	25
Version	adjustable end position damping
A (piston rod thread)	M 12
B (fastening thread)	M 38x1,5

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

G (compressed air port)	G 1/4"
B1 [mm]	8
B2 [mm]	42
D1 [mm]	50
D2 [mm]	16
D4 [mm]	46
D5 [mm]	38
D6 [mm]	41,6
D7	M 10x1
F [mm]	24
K [mm]	45
L1 [mm]	172
L2 [mm]	57
L3 [mm]	87
L4 [mm]	35
L5 [mm]	16
CH [mm]	12