

Airtec DSWPVM 50/160. Round cylinder, piston 50 mm, stroke 160 mm

Item no. FL-DSWPVM-50/160

Manufacturer Airtec

EAN 4050571276355

Round cylinder, piston 50 mm, stroke 160 mm

TECHNICAL DATA

HS-Code 84123100

Weight 2 kg



DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: hard chromium plated steel, seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

Piston diameter [mm]	50
Stroke [mm]	160
Version	adjustable end position damping
A (piston rod thread)	M 16
B (fastening thread)	M 45x1,5

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

G (compressed air port)	G 1/4"
B1 [mm]	9
B2 [mm]	53
D1 [mm]	58
D2 [mm]	20
D4 [mm]	57
D5 [mm]	45
D6 [mm]	52,4
D7	M 12x1,5
F [mm]	32
K [mm]	50
L1 [mm]	188
L2 [mm]	62
L3 [mm]	96
L4 [mm]	38
L5 [mm]	18
CH [mm]	16