

## Airtec DSWPVM 50/250. Round cylinder, piston 50 mm, stroke 250 mm

Item no. FL-DSWPVM-50/250

Manufacturer Airtec

EAN 4050571276386

Round cylinder, piston 50 mm, stroke 250 mm

### TECHNICAL DATA

HS-Code **84123100**

Weight **2.4 kg**



### DESCRIPTION

Materials:

Head and foot: anodized aluminium, cylinder tube: 1.4301, piston rod: hard chromium plated steel, seal: NBR / PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D in combination with fastening D1, C in combination with fastening C1

|                       |                                 |
|-----------------------|---------------------------------|
| Piston diameter [mm]  | 50                              |
| Stroke [mm]           | 250                             |
| Version               | adjustable end position damping |
| A (piston rod thread) | M 16                            |
| B (fastening thread)  | M 45x1,5                        |

|                         |          |
|-------------------------|----------|
| G (compressed air port) | G 1/4"   |
| B1 [mm]                 | 9        |
| B2 [mm]                 | 53       |
| D1 [mm]                 | 58       |
| D2 [mm]                 | 20       |
| D4 [mm]                 | 57       |
| D5 [mm]                 | 45       |
| D6 [mm]                 | 52,4     |
| D7                      | M 12x1,5 |
| F [mm]                  | 32       |
| K [mm]                  | 50       |
| L1 [mm]                 | 188      |
| L2 [mm]                 | 62       |
| L3 [mm]                 | 96       |
| L4 [mm]                 | 38       |
| L5 [mm]                 | 18       |
| CH [mm]                 | 16       |