

## Airtec NAD 100/100. ISO 21287 cylinders, double acting, piston 100 mm, stroke 100 mm

Item no. FL-NAD-100/100

Manufacturer Airtec

EAN 4050571516604

ISO 21287 cylinders, double acting, piston 100 mm, stroke 100 mm

### TECHNICAL DATA

HS-Code 84123100

Norm ISO 21287

Weight 3 kg



### STANDARDS & COMPLIANCE

ISO 21287

### DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                               |                             |
|-------------------------------|-----------------------------|
| Piston diameter [mm]          | 100                         |
| Stroke [mm]                   | 100                         |
| Version                       | Standard                    |
| KF (piston rod female thread) | M 12                        |
| G (compressed air port)       | G 1/8"                      |
| Repair sets                   | <a href="#">NAD 100 REP</a> |
| A [mm]                        | 25                          |
| AF [mm]                       | 20                          |
| B [mm]                        | 12                          |
| BG [mm]                       | 19,5                        |
| CH [mm]                       | 21                          |
| E [mm]                        | 113,5                       |
| LA [mm]                       | 3,0                         |
| RT                            | M 10                        |
| TG [mm]                       | 89,0                        |
| WH [mm]                       | 10                          |
| ZA [mm]                       | 67                          |
| ZB [mm]                       | 77                          |
| ZC [mm]                       | 46                          |