

Airtec NAD 20/40-AG. ISO 21287 cylinders, double acting, piston 20 mm, stroke 40 mm

Item no. FL-NAD-20/40-AG

Manufacturer Airtec

EAN 4050571517137

ISO 21287 cylinders, double acting, piston 20 mm, stroke 40 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.23 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	20
Stroke [mm]	40
Version	Piston rod with male thread
KK (piston rod male thread)	M 8
G (compressed air port)	M 5
Repair sets	NAD 20 REP
A [mm]	10
AK [mm]	16
B [mm]	9
BG [mm]	19,5
CH [mm]	9
E [mm]	36,0
LA [mm]	4,5
RT	M 5
TG [mm]	22,0
WH [mm]	6
ZA [mm]	37
ZB [mm]	43
ZC [mm]	22