

Airtec NAD 32/30-AG. ISO 21287 cylinders, double acting, piston 32 mm, stroke 30 mm

Item no. FL-NAD-32/30-AG

Manufacturer Airtec

EAN 4050571517717

ISO 21287 cylinders, double acting, piston 32 mm, stroke 30 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.35 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	32
Stroke [mm]	30
Version	Piston rod with male thread
KK (piston rod male thread)	M 10x1,25
G (compressed air port)	G 1/8"
Repair sets	NAD 32 REP
A [mm]	12
AK [mm]	19
B [mm]	9
BG [mm]	14,0
CH [mm]	10
E [mm]	49,0
LA [mm]	4,5
RT	M 6
TG [mm]	32,5
WH [mm]	7
ZA [mm]	44
ZB [mm]	51
ZC [mm]	29