

## Airtec NAD 40/125-AG. ISO 21287 cylinders, double acting, piston 40 mm, stroke 125 mm

Item no. FL-NAD-40/125-AG

Manufacturer Airtec

EAN 4050571517892

ISO 21287 cylinders, double acting, piston 40 mm, stroke 125 mm

### TECHNICAL DATA

|         |                      |
|---------|----------------------|
| HS-Code | 84123100             |
| Norm    | ISO 15552, ISO 21287 |
| Weight  | 0.7 kg               |



### STANDARDS & COMPLIANCE

ISO 21287

### DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

**esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                             |                             |
|-----------------------------|-----------------------------|
| Piston diameter [mm]        | 40                          |
| Stroke [mm]                 | 125                         |
| Version                     | Piston rod with male thread |
| KK (piston rod male thread) | M 10x1,25                   |
| G (compressed air port)     | G 1/8"                      |
| Repair sets                 | <a href="#">NAD 40 REP</a>  |
| A [mm]                      | 12                          |
| AK [mm]                     | 19                          |
| B [mm]                      | 9                           |
| BG [mm]                     | 14,5                        |
| CH [mm]                     | 10                          |
| E [mm]                      | 54,5                        |
| LA [mm]                     | 5,0                         |
| RT                          | M 6                         |
| TG [mm]                     | 38,0                        |
| WH [mm]                     | 7                           |
| ZA [mm]                     | 45                          |
| ZB [mm]                     | 52                          |
| ZC [mm]                     | 29                          |