

Airtec NAD 50/25. ISO 21287 cylinders, double acting, piston 50 mm, stroke 25 mm

Item no.	FL-NAD-50/25	Manufacturer	Airtec
Manufacturer no.	NAD 50/25	EAN	4050571518318

ISO 21287 cylinders, double acting, piston 50 mm, stroke 25 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	55 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

Piston rod with male thread -**male thread**

Piston diameter [mm]	50
Stroke [mm]	25
Version	Standard
KF (piston rod female thread) M 10	
G (compressed air port)	G 1/8"
Repair sets	NAD 50 REP
A [mm]	16
AF [mm]	16
B [mm]	12
BG [mm]	14,5
CH [mm]	13
E [mm]	65,5
LA [mm]	5,0
RT	M 8
TG [mm]	46,5
WH [mm]	8
ZA [mm]	45
ZB [mm]	53
ZC [mm]	29