

Airtec NAD 63/20-AG. ISO 21287 cylinders, double acting, piston 63 mm, stroke 20 mm

Item no. FL-NAD-63/20-AG

Manufacturer Airtec

EAN 4050571518639

ISO 21287 cylinders, double acting, piston 63 mm, stroke 20 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.75 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	63
Stroke [mm]	20
Version	Piston rod with male thread
KK (piston rod male thread)	M 12x1,25
G (compressed air port)	G 1/8"
Repair sets	NAD 63 REP
A [mm]	16
AK [mm]	22
B [mm]	12
BG [mm]	13,8
CH [mm]	13
E [mm]	77,0
LA [mm]	5,0
RT	M 8
TG [mm]	56,5
WH [mm]	8
ZA [mm]	49
ZB [mm]	57
ZC [mm]	34