

Airtec NAD 80/80-AG. ISO 21287 cylinders, double acting, piston 80 mm, stroke 80 mm

Item no. FL-NAD-80/80-AG

Manufacturer Airtec

EAN 4050571519186

ISO 21287 cylinders, double acting, piston 80 mm, stroke 80 mm

TECHNICAL DATA

HS-Code 84123100

Weight 1.8 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	80
Stroke [mm]	80
Version	Piston rod with male thread
KK (piston rod male thread)	M 16x1,5
G (compressed air port)	G 1/8"
Repair sets	NAD 80 REP
A [mm]	20
AK [mm]	28
B [mm]	12
BG [mm]	15,0
CH [mm]	17
E [mm]	95,5
LA [mm]	3,0
RT	M 10
TG [mm]	72,0
WH [mm]	10
ZA [mm]	54
ZB [mm]	64
ZC [mm]	38