

Airtec NADA 100/150. ISO 21287 cylinders, double acting, piston 100 mm, stroke 150 mm

Item no. FL-NADA-100/150

Manufacturer Airtec

EAN 4050571519247

ISO 21287 cylinders, double acting, piston 100 mm, stroke 150 mm

TECHNICAL DATA

HS-Code 84123100

Weight 1 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	100
Stroke [mm]	150
Version	non-rotating piston rod
G (compressed air port)	G 1/8"
Repair sets	NAD 100 REP
A [mm]	25
B [mm]	12
BG [mm]	19,5
CH [mm]	21
D [mm]	30
D1 [mm]	80
D2	M 10
D3 [mm]	10
E [mm]	113,5
LA [mm]	3,0
RT	M 10
TG [mm]	89,0
WH [mm]	10
ZA [mm]	67
ZC [mm]	46
ZD [mm]	91