

# Airtec NADA 100/40. ISO 21287 cylinders, double acting, piston 100 mm, stroke 40 mm

<b>Item no.</b>	FL-NADA-100/40	<b>Manufacturer</b>	Airtec
<b>Manufacturer no.</b>	NADA 100/40	<b>EAN</b>	4050571519322

ISO 21287 cylinders, double acting, piston 100 mm, stroke 40 mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>1 kg</b>



## STANDARDS & COMPLIANCE

**ISO 21287**

## DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

**esd.equipment**

Keldersstr. 15  
42697 Solingen, Deutschland  
VAT ID: DE269659389

Phone: +49 212 38340680  
shop@esd-equipment.com

**esd.equipment**

Page 1/2

## Piston rod with male thread **-male thread**

Piston diameter [mm]	100
Stroke [mm]	40
Version	non-rotating piston rod
G (compressed air port)	G 1/8"
Repair sets	<a href="#">NAD 100 REP</a>
A [mm]	25
B [mm]	12
BG [mm]	19,5
CH [mm]	21
D [mm]	30
D1 [mm]	80
D2	M 10
D3 [mm]	10
E [mm]	113,5
LA [mm]	3,0
RT	M 10
TG [mm]	89,0
WH [mm]	10
ZA [mm]	67
ZC [mm]	46
ZD [mm]	91