

Airtec NADA 20/40. ISO 21287 cylinders, double acting, piston 20 mm, stroke 40 mm

Item no. FL-NADA-20/40

Manufacturer Airtec

EAN 4050571519469

ISO 21287 cylinders, double acting, piston 20 mm, stroke 40 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.27 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	20
Stroke [mm]	40
Version	non-rotating piston rod
G (compressed air port)	M 5
Repair sets	NAD 20 REP
A [mm]	10
B [mm]	9
BG [mm]	19,5
CH [mm]	9
D [mm]	11
D1 [mm]	17
D2	M 4
D3 [mm]	4
E [mm]	36,0
LA [mm]	4,5
RT	M 5
TG [mm]	22,0
WH [mm]	6
ZA [mm]	37
ZC [mm]	22
ZD [mm]	51