

Airtec NADA 25/100. ISO 21287 cylinders, double acting, piston 25 mm, stroke 100 mm

Item no. FL-NADA-25/100

Manufacturer Airtec

EAN 4050571519520

ISO 21287 cylinders, double acting, piston 25 mm, stroke 100 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.5 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	25
Stroke [mm]	100
Version	non-rotating piston rod
G (compressed air port)	M 5
Repair sets	NAD 25 REP
A [mm]	10
B [mm]	9
BG [mm]	19,5
CH [mm]	9
D [mm]	14
D1 [mm]	22
D2	M 5
D3 [mm]	5
E [mm]	40,0
LA [mm]	4,5
RT	M 5
TG [mm]	26,0
WH [mm]	6
ZA [mm]	39
ZC [mm]	24
ZD [mm]	53