

Airtec NADA 32/60. ISO 21287 cylinders, double acting, piston 32 mm, stroke 60 mm

Item no. FL-NADA-32/60

Manufacturer Airtec

EAN 4050571519780

ISO 21287 cylinders, double acting, piston 32 mm, stroke 60 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.5 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	32
Stroke [mm]	60
Version	non-rotating piston rod
G (compressed air port)	G 1/8"
Repair sets	NAD 32 REP
A [mm]	12
B [mm]	9
BG [mm]	14,0
CH [mm]	10
D [mm]	17
D1 [mm]	28
D2	M 5
D3 [mm]	5
E [mm]	49,0
LA [mm]	4,5
RT	M 6
TG [mm]	32,5
WH [mm]	7
ZA [mm]	44
ZC [mm]	29
ZD [mm]	61