

# Airtec NADA 80/150. ISO 21287 cylinders, double acting, piston 80 mm, stroke 150 mm

<b>Item no.</b>	FL-NADA-80/150	<b>Manufacturer</b>	Airtec
<b>Manufacturer no.</b>	NADA 80/150	<b>EAN</b>	4050571520328

ISO 21287 cylinders, double acting, piston 80 mm, stroke 150 mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>31 kg</b>



## STANDARDS & COMPLIANCE

**ISO 21287**

## DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

## Piston rod with male thread **-male thread**

Piston diameter [mm]	80
Stroke [mm]	150
Version	non-rotating piston rod
G (compressed air port)	G 1/8"
Repair sets	<a href="#">NAD 80 REP</a>
A [mm]	20
B [mm]	12
BG [mm]	15,0
CH [mm]	17
D [mm]	28
D1 [mm]	65
D2	M 8
D3 [mm]	8
E [mm]	95,5
LA [mm]	3,0
RT	M 10
TG [mm]	72,0
WH [mm]	10
ZA [mm]	54
ZC [mm]	38
ZD [mm]	78