

## Airtec NAE 20/25. ISO 21287 cylinders, single acting, piston 20 mm, stroke 25 mm

Item no. FL-NAE-20/25

Manufacturer Airtec

EAN 4050571521110

ISO 21287 cylinders, single acting, piston 20 mm, stroke 25 mm

### TECHNICAL DATA

HS-Code 84123100

Weight 0.185 kg



### STANDARDS & COMPLIANCE

ISO 21287

### DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

|                               |                            |
|-------------------------------|----------------------------|
| Piston diameter [mm]          | 20                         |
| Stroke [mm]                   | 25                         |
| Version                       | Standard                   |
| KF (piston rod female thread) | M 6                        |
| G (compressed air port)       | M 5                        |
| Repair sets                   | <a href="#">NAD 20 REP</a> |
| A [mm]                        | 10                         |
| AF [mm]                       | 10                         |
| B [mm]                        | 9                          |
| BG [mm]                       | 19,5                       |
| CH [mm]                       | 9                          |
| E [mm]                        | 36,0                       |
| LA [mm]                       | 4,5                        |
| RT                            | M 5                        |
| TG [mm]                       | 22,0                       |
| WH [mm]                       | 6                          |
| ZA [mm]                       | 37                         |
| ZB [mm]                       | 43                         |
| ZC [mm]                       | 22                         |