

Airtec NAE 25/10. ISO 21287 cylinders, single acting, piston 25 mm, stroke 10 mm

Item no. FL-NAE-25/10

Manufacturer Airtec

EAN 4050571521165

ISO 21287 cylinders, single acting, piston 25 mm, stroke 10 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.185 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	25
Stroke [mm]	10
Version	Standard
KF (piston rod female thread)	M 6
G (compressed air port)	M 5
Repair sets	NAD 25 REP
A [mm]	10
AF [mm]	10
B [mm]	9
BG [mm]	19,5
CH [mm]	9
E [mm]	40,0
LA [mm]	4,5
RT	M 5
TG [mm]	26,0
WH [mm]	6
ZA [mm]	39
ZB [mm]	45
ZC [mm]	24