

Airtec NAE 80/20. ISO 21287 cylinders, single acting, piston 80 mm, stroke 20 mm

Item no. FL-NAEE-80/20

Manufacturer Airtec

EAN 4050571522568

ISO 21287 cylinders, single acting, piston 80 mm, stroke 20 mm

TECHNICAL DATA

HS-Code 84123100

Weight 1 kg



STANDARDS & COMPLIANCE

ISO 21287

DESCRIPTION

Materials:

Head and foot: Aluminium, cylinder tube: Anodized aluminium, piston rod: stainless steel, seal: NBR/PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread****esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Piston diameter [mm]	80
Stroke [mm]	20
Version	extended in idle position
KF (piston rod female thread)	M 12
G (compressed air port)	G 1/8"
Repair sets	NAD 80 REP
A [mm]	20
AF [mm]	20
B [mm]	12
BG [mm]	15,0
CH [mm]	17
E [mm]	95,5
LA [mm]	3,0
RT	M 10
TG [mm]	72,0
WH [mm]	10
ZA [mm]	54
ZB [mm]	64
ZC [mm]	38