

Airtec NXD 50/80. Compact cylinders, double acting, piston 50 mm, stroke 80 mm

Item no. FL-NXD-50/80

Manufacturer Airtec

EAN 4050571529093

Compact cylinders, double acting, piston 50 mm, stroke 80 mm

TECHNICAL DATA

HS-Code **84799070**

Weight **0.9 kg**



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	50
----------------------	----

Stroke [mm]	80
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	Standard
G1 (piston rod female thread)	M 8
M (compressed air port)	G 1/8"
Repair sets	NXD 50 REP
A [mm]	67
B [mm]	16
C [mm]	6
D [mm]	6,7
E	M 8
F [mm]	10,5
J [mm]	45,5
L [mm]	0
N [mm]	8,0
O [mm]	14,75
P [mm]	50
Q [mm]	12
T [mm]	13
U [mm]	6,5
Z [mm]	7,5