

Airtec NXDA 100/30. Compact cylinders, double acting, piston 100 mm, stroke 30 mm

Item no. FL-NXDA-100/30

Manufacturer Airtec

EAN 4050571529932

Compact cylinders, double acting, piston 100 mm, stroke 30 mm

TECHNICAL DATA

HS-Code **84799070**

Weight **3.4 kg**



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	100
----------------------	-----

Stroke [mm]	30
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	non-rotating piston rod
M (compressed air port)	G 1/4"
Repair sets	NXD 100 REP
A [mm]	124
B [mm]	25
C [mm]	8
D [mm]	8,5
E	M 10
F [mm]	13,5
G [mm]	30
H [mm]	14
I	M 10
J [mm]	66,5
K [mm]	10
L [mm]	0
N [mm]	10,5
O [mm]	19,25
P [mm]	103
R [mm]	80
S [mm]	56,6
T [mm]	22
U [mm]	8,5
W [mm]	10,0
X [mm]	3,0
Y [mm]	14
Z [mm]	10,0