

Airtec NXDA 20/10. Compact cylinders, double acting, piston 20 mm, stroke 10 mm

Item no. FL-NXDA-20/10

Manufacturer Airtec

EAN 4050571530150

Compact cylinders, double acting, piston 20 mm, stroke 10 mm

TECHNICAL DATA

HS-Code **84123100**

Weight **0.175 kg**



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm] 20

Stroke [mm] 10

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	non-rotating piston rod
M (compressed air port)	M 5
Repair sets	NXD 20 REP
A [mm]	36
B [mm]	10
C [mm]	6
D [mm]	4,2
E	M 5
F [mm]	7,5
G [mm]	11
H [mm]	5
I	M 4
J [mm]	38,0
K [mm]	4
L [mm]	0
N [mm]	8,0
O [mm]	12,25
P [mm]	22
R [mm]	17
S [mm]	12,0
T [mm]	8
U [mm]	4,5
W [mm]	5,0
X [mm]	1,5
Y [mm]	8
Z [mm]	4,5