

Airtec NXDA 25/30. Compact cylinders, double acting, piston 25 mm, stroke 30 mm

Item no. FL-NXDA-25/30

Manufacturer Airtec

EAN 4050571530372

Compact cylinders, double acting, piston 25 mm, stroke 30 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.28 kg



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	25
----------------------	----

Stroke [mm]	30
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	non-rotating piston rod
M (compressed air port)	M 5
Repair sets	NXD 25 REP
A [mm]	40
B [mm]	10
C [mm]	6
D [mm]	4,2
E	M 5
F [mm]	7,5
G [mm]	14
H [mm]	6
I	M 5
J [mm]	39,5
K [mm]	5
L [mm]	0
N [mm]	8,0
O [mm]	12,75
P [mm]	26
R [mm]	22
S [mm]	15,6
T [mm]	8
U [mm]	4,5
W [mm]	5,0
X [mm]	1,5
Y [mm]	8
Z [mm]	5,5