

Airtec NXDA 50/30. Compact cylinders, double acting, piston 50 mm, stroke 30 mm

Item no. FL-NXDA-50/30

Manufacturer Airtec

EAN 4050571530860

Compact cylinders, double acting, piston 50 mm, stroke 30 mm

TECHNICAL DATA

HS-Code 84799070

Weight 0.8 kg



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm] 50

Stroke [mm] 30

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	non-rotating piston rod
M (compressed air port)	G 1/8"
Repair sets	NXD 50 REP
A [mm]	67
B [mm]	16
C [mm]	6
D [mm]	6,7
E	M 8
F [mm]	10,5
G [mm]	22
H [mm]	10
I	M 6
J [mm]	45,5
K [mm]	6
L [mm]	0
N [mm]	8,0
O [mm]	14,75
P [mm]	50
R [mm]	42
S [mm]	29,7
T [mm]	13
U [mm]	6,5
W [mm]	7,5
X [mm]	2,5
Y [mm]	12
Z [mm]	7,5