

Airtec NXDK 16/30. Compact cylinders, double acting, piston 16 mm, stroke 30 mm

Item no. FL-NXDK-16/30

Manufacturer Airtec

EAN 4050571531485

Compact cylinders, double acting, piston 16 mm, stroke 30 mm

TECHNICAL DATA

HS-Code 84123100

Weight 0.145 kg



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	16
----------------------	----

Stroke [mm]	30
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	continuous piston rod
G1 (piston rod female thread)	M 4
M (compressed air port)	M 5
Repair sets	NXD 16 REP
A [mm]	29
B [mm]	8
C [mm]	6
D [mm]	3,3
E	M 4
F [mm]	6,0
J [mm]	38,0
N [mm]	8,0
O [mm]	12,25
P [mm]	18
Q [mm]	8
T [mm]	6
U [mm]	3,5
Z [mm]	4,5