

Airtec NXDK 20/5. Compact cylinders, double acting, piston 20 mm, stroke 5 mm

Item no.	FL-NXDK-20/5	Manufacturer	Airtec
Manufacturer no.	NXDK 20/5	EAN	4050571531652

Compact cylinders, double acting, piston 20 mm, stroke 5 mm

TECHNICAL DATA

Article authenticity	Original product
Condition of article	New
HS-Code	84123100
Weight	1 kg



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	20
Stroke [mm]	5
Version	continuous piston rod

G1 (piston rod female thread)	M 5
M (compressed air port)	M 5
Repair sets	NXD 20 REP
A [mm]	36
B [mm]	10
C [mm]	6
D [mm]	4,2
E	M 5
F [mm]	7,5
J [mm]	38,0
N [mm]	8,0
O [mm]	12,25
P [mm]	22
Q [mm]	10
T [mm]	8
U [mm]	4,5
Z [mm]	4,5