

## Airtec NXE 80/5. Compact cylinders, single acting, piston 80 mm, stroke 5 mm

Item no. FL-NXE-80/5

Manufacturer Airtec

EAN 4050571532956

Compact cylinders, single acting, piston 80 mm, stroke 5 mm

### TECHNICAL DATA

HS-Code 84123100

Weight 1.5 kg



### DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

|                      |    |
|----------------------|----|
| Piston diameter [mm] | 80 |
|----------------------|----|

|             |   |
|-------------|---|
| Stroke [mm] | 5 |
|-------------|---|

**esd.equipment**

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

**esd.equipment**

Page 1/2

| Version                       | Standard                   |
|-------------------------------|----------------------------|
| G1 (piston rod female thread) | M 10                       |
| M (compressed air port)       | G 1/8"                     |
| Repair sets                   | <a href="#">NXE 80 REP</a> |
| A [mm]                        | 100                        |
| B [mm]                        | 20                         |
| C [mm]                        | 8                          |
| D [mm]                        | 8,5                        |
| E                             | M 10                       |
| F [mm]                        | 13,5                       |
| J [mm]                        | 56,0                       |
| L [mm]                        | 0                          |
| N [mm]                        | 8,5                        |
| O [mm]                        | 16,00                      |
| P [mm]                        | 82                         |
| Q [mm]                        | 15                         |
| T [mm]                        | 17                         |
| U [mm]                        | 8,5                        |
| Z [mm]                        | 8,0                        |