

# Airtec NXEE 12/25. Compact cylinders, single acting, piston 12 mm, stroke 25 mm

<b>Item no.</b>	FL-NXEE-12/25	<b>Manufacturer</b>	Airtec
<b>Manufacturer no.</b>	NXEE 12/25	<b>EAN</b>	4050571533113

Compact cylinders, single acting, piston 12 mm, stroke 25 mm

## TECHNICAL DATA

Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84799070</b>
Weight	<b>12 kg</b>



## DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	12
Stroke [mm]	25
Version	extended in idle position

G1 (piston rod female thread)	M 3
M (compressed air port)	M 5
Repair sets	<a href="#">NXE 12 REP</a>
A [mm]	29
B [mm]	6
C [mm]	6
D [mm]	3,3
E	M 4
F [mm]	6,0
J [mm]	38,0
L [mm]	0
N [mm]	8,0
O [mm]	12,25
P [mm]	18
Q [mm]	6
T [mm]	5
U [mm]	3,5
Z [mm]	4,5