

Airtec NXEE 16/15. Compact cylinders, single acting, piston 16 mm, stroke 15 mm

Item no. FL-NXEE-16/15

Manufacturer Airtec

EAN 4050571533175

Compact cylinders, single acting, piston 16 mm, stroke 15 mm

TECHNICAL DATA

HS-Code 84799070

Weight 0.105 kg



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm] 16

Stroke [mm] 15

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	extended in idle position
G1 (piston rod female thread)	M 4
M (compressed air port)	M 5
Repair sets	NXE 16 REP
A [mm]	29
B [mm]	8
C [mm]	6
D [mm]	3,3
E	M 4
F [mm]	6,0
J [mm]	38,0
L [mm]	0
N [mm]	8,0
O [mm]	12,25
P [mm]	18
Q [mm]	8
T [mm]	6
U [mm]	3,5
Z [mm]	4,5