

Airtec NXEE 25/20-AG. Compact cylinders, single acting, piston 25 mm, stroke 20 mm

Item no. FL-NXEE-25/20-AG

Manufacturer Airtec

EAN 4050571533403

Compact cylinders, single acting, piston 25 mm, stroke 20 mm

TECHNICAL DATA

HS-Code	84123100
Weight	0.23 kg



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:
-20 to +80 °C

Operating pressure:
max. 10 bar

Version:
With Magnetic piston

Cylinder switch type:
D, A

Optional:
Piston rod with male thread **-male thread**

Piston diameter [mm]	25
Stroke [mm]	20

Version	Extended in idle position, piston rod with male thread
G2 (piston rod male thread)	M 10x1,25
M (compressed air port)	M 5
Repair sets	NXE 25 REP
A [mm]	40
C [mm]	6
D [mm]	4,2
E	M 5
F [mm]	7,5
J [mm]	39,5
L [mm]	0
N [mm]	8,0
O [mm]	12,75
P [mm]	26
Q [mm]	10
T [mm]	8
U [mm]	4,5
V [mm]	22
Z [mm]	5,5