

# Airtec NXEE 25/5. Compact cylinders, single acting, piston 25 mm, stroke 5 mm

|                         |              |                     |               |
|-------------------------|--------------|---------------------|---------------|
| <b>Item no.</b>         | FL-NXEE-25/5 | <b>Manufacturer</b> | Airtec        |
| <b>Manufacturer no.</b> | NXEE 25/5    | <b>EAN</b>          | 4050571533434 |

Compact cylinders, single acting, piston 25 mm, stroke 5 mm

## TECHNICAL DATA

|                      |                         |
|----------------------|-------------------------|
| Article authenticity | <b>Original product</b> |
| Condition of article | <b>New</b>              |
| HS-Code              | <b>84799070</b>         |
| Weight               | <b>175 kg</b>           |



## DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

|                      |                           |
|----------------------|---------------------------|
| Piston diameter [mm] | 25                        |
| Stroke [mm]          | 5                         |
| Version              | extended in idle position |

|                               |                            |
|-------------------------------|----------------------------|
| G1 (piston rod female thread) | M 5                        |
| M (compressed air port)       | M 5                        |
| Repair sets                   | <a href="#">NXE 25 REP</a> |
| A [mm]                        | 40                         |
| B [mm]                        | 10                         |
| C [mm]                        | 6                          |
| D [mm]                        | 4,2                        |
| E                             | M 5                        |
| F [mm]                        | 7,5                        |
| J [mm]                        | 39,5                       |
| L [mm]                        | 0                          |
| N [mm]                        | 8,0                        |
| O [mm]                        | 12,75                      |
| P [mm]                        | 26                         |
| Q [mm]                        | 10                         |
| T [mm]                        | 8                          |
| U [mm]                        | 4,5                        |
| Z [mm]                        | 5,5                        |