

Airtec NXEE 80/25. Compact cylinders, single acting, piston 80 mm, stroke 25 mm

Item no. FL-NXEE-80/25

Manufacturer Airtec

EAN 4050571533908

Compact cylinders, single acting, piston 80 mm, stroke 25 mm

TECHNICAL DATA

HS-Code **84799070**

Weight **1.7 kg**



DESCRIPTION

Materials:

Head and base: Anodized aluminium, cylinder tube: Anodized aluminium, piston rod: 1.4305, seal: PUR

Temperature range:

-20 to +80 °C

Operating pressure:

max. 10 bar

Version:

With Magnetic piston

Cylinder switch type:

D, A

Optional:

Piston rod with male thread **-male thread**

Piston diameter [mm]	80
----------------------	----

Stroke [mm]	25
-------------	----

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

Version	extended in idle position
G1 (piston rod female thread)	M 10
M (compressed air port)	G 1/8"
Repair sets	NXE 80 REP
A [mm]	100
B [mm]	20
C [mm]	8
D [mm]	8,5
E	M 10
F [mm]	13,5
J [mm]	56,0
L [mm]	0
N [mm]	8,5
O [mm]	16,00
P [mm]	82
Q [mm]	15
T [mm]	17
U [mm]	8,5
Z [mm]	8,0