

Airtec XL 32/900. ISO 15552 cylinders, piston 32 mm, stroke 900 mm

Item no. FL-XL-32/900

Manufacturer Airtec

EAN 4050571798192

ISO 15552 cylinders, piston 32 mm, stroke 900 mm

TECHNICAL DATA

HS-Code	84123100
Norm	ISO 15552, ISO 6431
Weight	3.2 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

esd.equipment

Keldersstr. 15
42697 Solingen, Deutschland
VAT ID: DE269659389

Phone: +49 212 38340680
shop@esd-equipment.com

esd.equipment

Page 1/2

D, A

Piston diameter [mm]	32
Stroke [mm]	900
Version	Standard
A (thread)	M 10x1,25
G (compressed air port)	G 1/8"
Repair sets	XL 32 REP
B [mm]	12
C [mm]	30
D [mm]	18,0
F [mm]	22
G [mm]	26
H [mm]	120
K [mm]	4
M [mm]	47,0
N [mm]	32,5
CH [mm]	10
RT	M 6