

Airtec XL 40/250. ISO 15552 cylinders, piston 40 mm, stroke 250 mm

Item no. **FL-XL-40/250** Manufacturer **Airtec**
Manufacturer no. **XL 40/250** EAN **4050571798406**

ISO 15552 cylinders, piston 40 mm, stroke 250 mm

TECHNICAL DATA

| | |
|----------------------|-------------------------|
| Article authenticity | Original product |
| Condition of article | New |
| HS-Code | 84123100 |
| Weight | 19 kg |



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A

| | |
|-------------------------|---------------------------|
| Piston diameter [mm] | 40 |
| Stroke [mm] | 250 |
| Version | Standard |
| A (thread) | M 12x1,25 |
| G (compressed air port) | G 1/4" |
| Repair sets | XL 40 REP |
| B [mm] | 16 |
| C [mm] | 35 |
| D [mm] | 22,0 |
| F [mm] | 24 |
| G [mm] | 30 |
| H [mm] | 135 |
| K [mm] | 4 |
| M [mm] | 54,0 |
| N [mm] | 38,0 |
| CH [mm] | 13 |
| RT | M 6 |