

Airtec XL 63/300. ISO 15552 cylinders, piston 63 mm, stroke 300 mm

Item no. FL-XL-63/300

Manufacturer Airtec

EAN 4050571799373

ISO 15552 cylinders, piston 63 mm, stroke 300 mm

TECHNICAL DATA

HS-Code 84123100

Weight 3.7 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

esd.equipment

Keldersstr. 15

42697 Solingen, Deutschland

VAT ID: DE269659389

Phone: +49 212 38340680

shop@esd-equipment.com

esd.equipment

Page 1/2

D, A

Piston diameter [mm]	63
Stroke [mm]	300
Version	Standard
A (thread)	M 16x1,5
G (compressed air port)	G 3/8"
Repair sets	XL 63 REP
B [mm]	20
C [mm]	45
D [mm]	25,0
F [mm]	32
G [mm]	37
H [mm]	158
K [mm]	4
M [mm]	74,0
N [mm]	56,5
CH [mm]	17
RT	M 8