

# Airtec XL 80/600-EK. ISO 15552 cylinders, piston 80 mm, stroke 600 mm

<b>Item no.</b>	FL-XL-80/600-EK	<b>Manufacturer</b>	Airtec
<b>Manufacturer no.</b>	XL 80/600-EK	<b>EAN</b>	4050571799991

ISO 15552 cylinders, piston 80 mm, stroke 600 mm

## TECHNICAL DATA



Article authenticity	<b>Original product</b>
Condition of article	<b>New</b>
HS-Code	<b>84123100</b>
Weight	<b>8 kg</b>

## STANDARDS & COMPLIANCE

**ISO 15552**

## DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A

Piston diameter [mm]	80
Stroke [mm]	600
Version	Stainless steel piston rods
A (thread)	M 20x1,5
G (compressed air port)	G 3/8"
Repair sets	<a href="#">XL 80 REP</a>
B [mm]	25
C [mm]	45
D [mm]	35,0
F [mm]	40
G [mm]	46
H [mm]	174
K [mm]	4
M [mm]	93,5
N [mm]	72,0
CH [mm]	22
RT	M 10