

Airtec XLK 125/25. ISO 15552 cylinders, piston 125 mm, stroke 25 mm

Item no. FL-XLK-125/25

Manufacturer Airtec

EAN 4050571801748

ISO 15552 cylinders, piston 125 mm, stroke 25 mm

TECHNICAL DATA

HS-Code 84123100

Weight 1 kg



STANDARDS & COMPLIANCE

ISO 15552

DESCRIPTION

Materials:

Head and foot: stove-enamelled die-cast aluminium, cylinder tube: anodized aluminium profile tube, piston rod: hard chromium plated steel, piston: complete piston (ST / NBR), seal: NBR / PUR

Temperature range:

-20°C to +80°C

Operating pressure:

max. 10 bar

Optional:

FKM seals (temperature range: -10°C to max. +150°C, without magnetic piston) **-V**, stainless steel piston rod **-EK**, ATEX approval Ex II 2GD c T5 T100° -20°C ≤ Ta ≤ 80°C **-X**

Version:

with magnetic pistons and adjustable end position damping

Cylinder switch type:

D, A

Piston diameter [mm]	125
Stroke [mm]	25
Version	continuous piston rod
A (thread)	M 27x2
G (compressed air port)	G 1/2"
Repair sets	XL 125 REP
B [mm]	32
C [mm]	60
D [mm]	46,0
F [mm]	54
G [mm]	65
H [mm]	225
K [mm]	6
M [mm]	137,5
N [mm]	110,0
CH [mm]	27
RT	M 12